

Chemical Safety Data Sheet

JLB005 Waterborne High Build One coat paint MSDS

1 Chemical and Enterprise Identification

Trade Name Waterborne Paste One coat paint

Manufacturer: Anping Jinlong Vehicle Equipment Co., Ltd.

Address: East of Jingsi Road, Anping Industrial Park (East Section), Anping County

Emergency Phone Number: +86(0)3187870062

Email: apjinlong163@163.com

Postcode: 053600

2 Component Information

Main Component	Content%		
Waterborne Resin	51.5%		
Pure Water	15%		
Additive	4.1%		
Iron oxide black	15%		
Precipitated barium sulfate	8%		
Aluminum hydroxide	5%		
Zinc Phosphate	0.9%		
Zinc oxide	0.8%		

No harmful substances

3 Hazard overview

Hazard class: R20/21/22

Routes of entry: Inhalation, skin, eyes, ingestion

Health Hazards:

Eye Contact: Eye Contact may cause eye irritation, redness, tearing, and blurred vision. **Inhalation:** Inhalation of paint mist can cause nasal and respiratory irritation, dizziness, weakness, tiredness, nausea, and headache.

Skin Contact: Skin contact may cause skin irritation, dermatitis as well as chapped and defatted skin with continued exposure.

Intake: Accidentally intake can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

4 First Aid Measures

Eye Contact: Flush with running water for 15 minutes and seek medical attention if irritation continues.

Inhalation of paint mist: quickly move to fresh air for a comfortable breathing, perform oxygen therapy if breathing is difficult, perform artificial respiration immediately and seek medical attention if breathing stops.

Skin Contact: Remove contaminated clothing immediately, rinse with plenty of running water, soapy water or special detergent.

Intake: Drink plenty of warm water, do not induce vomiting, seek medical attention.

5 Firefighting measures

Flammability: This product is waterborne and non-flammable.

6 ACCIDENTAL RELEASE MEASURES

It is recommended that emergency personnel wear rubber gloves and protective clothing. Do not come into direct contact with spillage. Small spills: covered spill with sand and soil, it can be disposed as household waste or general non-hazardous chemical waste after drying. Large spills: Cover spill with plastic sheeting or canvas to reduce volatilization. Remove under expert guidance.

7 Operation and storage

Handling Precautions: Provide proper ventilation to avoid eye and skin from contacting. It should be handled with care to prevent damage to packaging and containers.

8 Protective measures

Occupational exposure limits in workplace

Iron oxide black

China: No regulation.

Barium sulfate

China: No regulation. Waterborne Resin Emulsion

China: No regulation.

Engineering Controls: General ventilation or local exhaust.

Respiratory system protection: Generally, no special protection is required, and a ventilated mask or a self-priming filter gas mask can be worn when exposed to high concentrations products.

Eye Protection: Wear chemical safety goggles.

Body Protection: Wear general work protective clothing.

Hand Protection: Wear chemical resistant gloves.

Other protection: Take shower and change clothes after work to avoid long-term

repeated contact.

9 Physical and chemical properties

Appearance & Properties: Black (or colored) Viscous Liquid

Relative Density (water=1, g/cm3): approx. 1.25

Solubility: Miscible in water

10 Stability & Reactivity

Stability: stable

Hazards of Aggregation: No Aggregation Contraindications: No information available

Combustion (decomposition) products: CO₂, H₂O.

11 Toxicological information

Acute toxicity

Iron oxide black

No data.

Barium sulfate

No data.

Waterborne Resin Emulsion

No data.

Irritating

Excessive exposure to paint steam or paint mist can cause eye and skin irritation and sometimes dermatitis.

12 Ecological Information

Ecotoxicity: No specific information available. This product cannot be poured directly

into the sewer.

Biodegradability: No information available

Non-biodegradability: No information available

13 Waste Disposal

Waste properties: non-hazardous waste

Waste Disposal Method: it can be disposed of as domestic waste or general

non-hazardous chemicals after drying.

Disposal method: Please consult the environmental protection department of the local government.

14 Transport

Domestic

Hazard Code: No information

Packaging Mark: Non-hazardous Goods

Packing Group: 20L plastic or iron drum

15 Regulatory Information

Product &	Chinese	Grading, Classification of	List of Dangerous	Identification of major
1 Toduct &	Cilliese	Grading, Classification of	List of Dangerous	hazards source

Component's	Current	Hypertoxic Substance &	Goods	GB18218-2000
Chemical Name	Chemical List	Production Name Code	GB12268-90	
		GB57-93		
Precipitated barium sulfate	YES	Not Applicable	Not Applicable	No regulation.
Waterborne Resin Emulsion	YES	Not Applicable	Not Applicable	No regulation.
Pure Water	No	Not Applicable	Not Applicable	No regulation.

16 Other information

The information states in this Material Safety Data Sheet has been prepared based on our current know-how and current national laws.

Products may not be used for purposes other than the one stated in product data sheets without prior written notice.

It is always the responsibility of the user to take the necessary measures to comply with the requirements of the applicable regulations.